## **DL-B1 Beveled Intelligent Laser Marking Machine**

| Image   Image                |                               |   |              |  |
|------------------------------|-------------------------------|---|--------------|--|
|                              |                               |   |              |  |
| -                            | Laser Model                   | MFP-20X/20QS  | MFP-30X/30QS |  |
|                              | Power                         | 18.5/20W  | 30W          |  |
| _                            | Beam Mass                     | ≤1.4  | ≤1.4         |  |
| Parameters -                 | Pulse Repetition<br>Frequency | 27-60 kHz   | 30-60 kHz    |  |
|                              | Laser Wavelength              | 1064±5 nm   |              |  |
|                              | Output Power<br>Stability     | <3%   |              |  |
|                              | Design Life                   | Around 100000 working hour (non-serviceable)                        |              |  |
|                              | Marking Range                 | $100 \sim 150 \mathrm{mm}(\mathrm{Range \ selectable})$             |              |  |
|                              | Depth of<br>Engraving         | $\leq 1  \text{mm}(\text{Depends on power and time})$               |              |  |
| Optical<br>Properties        | Engraving Speed               | $\leq 10000 mm/s$   |              |  |
| -                            | Repeatability                 | ±0.002  |              |  |
|                              | Minimum Marker<br>Line Width  | 0.1mm   |              |  |
|                              | Minimum character<br>height   | 0.15mm  |              |  |
| Operating<br>Environme<br>nt | Cooling Methods               | Built-in air-cooling  |              |  |
|                              | System Power<br>Supply        | 500W / 220V / 50Hz(Can be connected with 110V)                      |              |  |
|                              | Temperature and humidity      | 0~40°, 30%≤RH≤85%,Air conditioning is required for out-of-range use |              |  |
|                              | Oil mist,<br>Condensation     | Not allowed   |              |  |
|                              | Operating System              | Windows Operation System  |              |  |
|                              | File Formats                  | All fonts/typefaces of WINDOWS OS font library (standard USB input) |              |  |

| Other<br>Parameters | External<br>Dimensions      | 460X300X683 mm |
|---------------------|-----------------------------|----------------|
|                     | Packing Size 550X440X690 mm |                |
|                     | Gross Weight                | Around 25kg    |